



GT310

Portable GPS Tracker



GPS+AGPS+LBS positioning

Allow the location to be pinpointed accurately and rapidly



Voice monitor

Activate listen-in mode via text



SOS call

Thumb sized button allowing urgent call during an emergency case



IP65 waterproof grade

Water-resistant design ensures stable operation in tough environment



Two-way talk

With MIC and speaker connected, it's easy to realize two-way audio



Fall alarm

Alarm will be sent if fall is detected

Application



Personal safety



Camping



Lone worker protection

GSM Specification

GSM frequency	850/900/1800/1900 MHz
GPRS	Class 12, TCP/IP
Memory	32+32Mb
Phase error	RMSPE<5,PPE<20
Max output	GSM850/GSM900:33±3dBm GSM1800/GSM1900:30±3dBm
Max frequency error	±0.1ppm
Receiving sensitivity	Class II RBER2%(-106dBm)

GPS Specification

GPS chipset	High sensitivity chip
Frequency	L1,1575.42MHz C/A code
GPS channel	66
Location accuracy	<10 meters
Tracking sensitivity	-165dBm
Acquisition sensitivity	-148dBm
TTF (open sky)	Avg. hot start ≤ 1sec Avg. cold start ≤ 32sec

Other Specifications

Voice monitor range	≤ 5 meters
Button	1xSOS, 1xPower On/Off
Antenna	Built-in quad-band GSM antenna, GPS ceramic antenna
LED	Status LED
Charger voltage/current	5VDC/1A
Operating temperature	-20°C ~ 70°C
Battery	900mAh/3.8V
Working time	6 days (Wi-Fi positioning, location data uploaded at 10 minutes interval)
Waterproof grade	IP65
Dimension	69.0(L)*41.0(W)*16.0(H)mm
Weight	70g

Contact

Jimi Electronic Co., Ltd.
Shenzhen Concox Information Technology Co., Ltd.

Add: 4/F, Building B, Gaoxinqi Industrial Park, Liuxian 1st Road, No.67 Bao'an District, Shenzhen

Tel: +86 755 6664 2520

Web: www.iconcox.com www.jimilab.com

Email: info@concox.cn info@jimilab.com