

Portable and Magnetic Vehicle GPS Tracker

Size		Overlook	
Product Type	Magnetic GPS Tracker No-wired GPS Tracker		
Battery capacity	1200/3400/7800mA		
Application	Valuable Assets		
	All kinds of vehicles		
Product Functions		Performance and Parameters	
<p>Main function</p> <ul style="list-style-type: none"> *Free installation without any process *With strong magnet, easy to stick to any iron *Real time positioning tracking vehicle anywhere *Applicable to any kind of cars, no cars limit option *Built-in MIC, Listen to live sounds remotely *Movement sensation alarm/Over speed alarm/Vibration alarm/Demolition alarm/Low power alarm/Offline alarm/Geofence alarm *Three working modes option (Deep sleep working mode, Intelligent sleep mode, Normal mode) *Flexible standby time after full charge 1200mA: 30 days standby time 3400mA: 180 days standby time 7800mA: 360 days standby time 		GSM baseband IC	MTK MT2503+RDA6625E
		GPS IC	Ublox G7020
		GSM band	850/900/1800/1900MHz
		GPRS	Class12
		GPS signal	L1, 1575.42MHz C/A code
		GPS channels	22 channels
		GPS fixed Time with AGPS	Cold start 15s, hot start 2s
		GPS receiving sensitivity	Tracking: -165dBm, Capturing: -159dBm
		GPS positioning accuracy	5-15m
		Minimum standby current	<0.5mA
		Average standby current	<2.5mA
		Average working current	<55mA
		Working temperature	-20~+70 centigrade
		Working humidity	5% to 95%
		GPS ANT	highly sensitive ANT
		GSM ANT	FPC antenna
G-sensor	Yes		
Microphone	Yes		
Shell material	ABS		

