

1	The main function	Support: Real-time GPS / BDS / WIFI / LBS positioning, SOS for help, remote monitoring, dialing the family number phone, electronic fence warning reminder,
2	chip	MT2503
3	Memory	32M Flash Memory
5	Equipment size	50*30*16mm
6	Working temperature	-20°C - +70°C
7	Working environment humidity	20%-80%RH
8	SIMcard	Card
9	GSM band	850MHz/900MHz/1800 MHz/1900MHz
10	GPRS	Class 12
11	battery	Charging 5V 3.7V 500mAh
12	Standby average current	Less than 2ma (determined by the connection method)
13	I / O interface	Built-in Micro 5pin
14	horn	0916 Specification AAC
15	MIC	High-definition silicon microphone (sound can be heard within 10 meters)
16	sensor	3D G-Sensor
17	TF	32G
18	GPS positioning accuracy	Within 10 meters
19	WIFI positioning accuracy	Within 50 meters
20	GSM positioning accuracy	≥5 meters
21	Speed accuracy	0.1 m / s
22	GPS positioning time	Cold start -38s (Open sky) Hot start -2s (Open sky) The specific time will be affected by the environment
24	GSM antenna	FPC antenna
26	Operating Voltage	3.5-4.2V (3.4V low power automatic shutdown)
28	GPS antenna	High Performance 15X15 Ceramic Antenna