

PARAMETER

Size	74mm(L)*32mm(W)*14mm(H)
Working Temperature	-20°C to 70°C
Working Voltage	9-90V

Weight 53g

HARDWARE SPECIFICATION

Location Accuracy	<=10m	Channel	20 Class
GPS Chip	MTK	GPS Sensitivity	-147dBm
GSM Frequency	850/900/1800/1900MHZ	Tracking Sensitivity	-163dBm
	Hot Start<2SEC(Open Sky)	Power LED Indicator	Red
Positioning Time	Warm Start<15SEC	GPS LED Indicator	Blue
	Cold Start<38SEC(Open Sky)	GSM LED Indicator	Green
GSM Antenna	Spring Antenna		
GPS Antenna	Built-in Ceramic Antenna		
GPRS	Class12, TCP/IP Built-in GSM Module		

SOFTWARE SPECIFICATION

ata Upgrade Port	Not Support	ACC Detection	Support
unction Port Definition	Not Support	Geo-fence	Support
arameter Setting	SMS Command, Platform	Cut-wire Alarm	Support
SPRS Upload	Upload Interval Every 10 Seconds	Vibration Alarm	Support
hird-party Checking	WEB/APP	Movement Alarm	Support

FUNCTION













APPLICATION







Fleet Management



Truck Tracking